

Metal

Synthetic antirust primer for metal works, can be painted over with synthetic enamels.



Mod. 51 Rev 64

Date of update 11/12/2019

CHARACTERISTICS:

METAL is a synthetic antirust primer, with excellent adhesion on metal, good anticorrosive power, matt finish that can be over-painted with nitro products.

USE:

METAL can be used as antirust on every kind of metal works, in buildings or industrial use. Due to its degree of gloss (very matt) it offers a high adhesion coefficient of the finishing coat on the primer. Used to paint railings, gates, iron doors, shutters etc.

PREPARATION AND APPLICATION:

By brush	Dilute with	Mineral spirits 5%
By spray	Dilute with	Mineral spirits 7 - 10%
By immersion	Dilute with	Mineral spirits 12 - 15%
Airbrush	Spray nozzle	mm 1,8
	Pressure	Atm 3-4

Apply on clean, degreased, untreated, rust-free metal sheet. It can be applied in 2 coats or it can be painted over with **GABBIANO**.

IMPORTANT NOTES:

- Before applying, make sure the support is perfectly dry and cured and perfectly anchored to the substratum, that it is not dirty, greasy, contaminated with mildew, fungi, bacteria, salts or anything else likely to prevent good adhesion and a successful result.
- Mix the product before use.
- Store in a cool, dry place away from sunlight at a temperature above +5°C.
- Use the product at room and surface temperature between + 5°C and + 35°C and with relative humidity not above 75%
- Avoid drying in environment or surface temperature below + 5°C
- Ensure to have enough coloured product of the same batch in order to complete the job or at least complete portions of it that will avoid drawing attention of differences in hues.
- Wash all tools with mineral spirit immediately after use.

TECHNICAL DATA:

Viscosity ford cup 8	14 ± 2 Sec
Specific weight	1,55 ± 0,15 kg/l
Solids	80 ± 2 %
Optimal thickness	50 ± 5 micron
Spreading rate	7 - 8 m ² /l
Appearance of the film	3-5 G (Matt)
Thinner	Paint thinner
Dust free	1-1,5 hours
Touch free	8 hours
Dry in depth	24 hours
Over painting	24 - 48 hours
Packages	2,5 l - 0,5 l
Colours	White, Grey RAL 7001, orange MINIO

Metal

Synthetic antirust primer for metal works, can be painted over with synthetic enamels.



Mod. 51 Rev 64
Date of update 11/12/2019

Classification: i/s) High performance monocomponent paints
Limit Phase II (from 01/01/ 2010): 500 g/l
VOC in preparation: < 500 g/l (max).

The above information has been obtained from scrupulously controlled tests, and represents our best and most recent knowledge. This information is provided for reference purposes only. It is not binding upon the manufacturer, and neither may it constitute grounds for any kind of complaint whatsoever associated with the use of the products described, also considering that the conditions of use are beyond our control.

Please refer to the relevant Safety Data Sheet.